



Standard	Type	Frequency	Voltage	Poles	Output HP	Frame	Locked rotor current (l/l/m)	Locked rotor torque	Breakdown torque	Moment of inertia	Locked rotor time	Weight	Noise level	Service Factor	Full load speed	Efficiency (%)			Power factor			Rated current	Altitude	Duty	Ambient temperature	Degree of Protection	
																50%	75%	100%	50%	75%	100%						
NEMA	ODP	60 Hz	208-230/460V	4	3	182T	Standard Frame	8.1	240%	300%	0.25415 sq.ft.lb	12 s	57.8 lb	dB(A)	1.15	1760 rpm	85.5	88.5	89.5	0.54	0.68	0.76	8.98/8.12/4.06 A	1000 m	S1	-20°C +40°C	IP21
NEMA	ODP	60 Hz	208-230/460V	4	5	184T	Standard Frame	7.3	210%	290%	0.34954 sq.ft.lb	12 s	61.7 lb	dB(A)	1.15	1755 rpm	88.5	89.5	89.5	0.63	0.75	0.81	14.2/12.8/6.41 A	1000 m	S1	-20°C +40°C	IP21
NEMA	ODP	60 Hz	208-230/460V	4	7.5	213/ST	Standard Frame	7.5	200%	270%	0.91977 sq.ft.lb	12 s	77.2 lb	dB(A)	1.15	1760 rpm	89	90.2	91	0.68	0.79	0.84	20.0/18.1/9.03 A	1000 m	S1	-20°C +40°C	IP21
NEMA	ODP	60 Hz	208-230/460V	4	10	213/ST	Standard Frame	6.3	210%	290%	1.19575 sq.ft.lb	6 s	124 lb	dB(A)	1.15	1765 rpm	90.2	91	91.7	0.64	0.76	0.84	27.0/24.4/12.2 A	1000 m	S1	-20°C +40°C	IP21
NEMA	ODP	60 Hz	208-230/460V	4	15	254T	Standard Frame	6.7	290%	300%	2.08397 sq.ft.lb	14 s	242 lb	59 dB(A)	1.15	1775 rpm	91.7	92.4	93	0.6	0.72	0.8	41.1/37.2/18.6 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	20	256T	Standard Frame	6.3	260%	280%	2.61979 sq.ft.lb	12 s	278 lb	60 dB(A)	1.15	1770 rpm	91.7	93	93	0.63	0.72	0.82	55.3/49.4/24.7 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	25	284T	Standard Frame	6.7	250%	280%	3.40549 sq.ft.lb	15 s	362 lb	62 dB(A)	1.15	1770 rpm	92.4	93	93.6	0.67	0.78	0.83	66.1/59.8/29.9 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	25	284TS	Standard Frame	6.7	250%	280%	3.40549 sq.ft.lb	15 s	342 lb	62 dB(A)	1.15	1770 rpm	92.4	93	93.6	0.67	0.78	0.83	66.1/59.8/29.9 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	30	286T	Standard Frame	6.7	260%	280%	4.89549 sq.ft.lb	14 s	394 lb	63 dB(A)	1.15	1770 rpm	93.6	94.1	94.1	0.7	0.8	0.83	78.3/70.8/35.4 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	30	286TS	Standard Frame	6.7	260%	280%	4.89549 sq.ft.lb	14 s	419 lb	63 dB(A)	1.15	1770 rpm	93.6	94.1	94.1	0.7	0.8	0.83	78.3/70.8/35.4 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	40	324T	Standard Frame	6.2	220%	230%	6.05399 sq.ft.lb	28 s	545 lb	64 dB(A)	1.15	1775 rpm	93.6	94.1	94.1	0.68	0.78	0.83	107.96/4/48.2 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	40	324TS	Standard Frame	6.2	220%	230%	6.05399 sq.ft.lb	28 s	507 lb	64 dB(A)	1.15	1775 rpm	93.6	94.1	94.1	0.68	0.78	0.83	107.96/4/48.2 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	50	326T	Standard Frame	6.3	240%	250%	7.03546 sq.ft.lb	12 s	564 lb	65 dB(A)	1.15	1775 rpm	94.1	94.5	94.5	0.7	0.79	0.82	132/120/59.9 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	50	326TS	Standard Frame	6.3	240%	250%	7.03546 sq.ft.lb	12 s	573 lb	65 dB(A)	1.15	1775 rpm	94.1	94.5	94.5	0.7	0.79	0.82	132/120/59.9 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	60	364T	Standard Frame	6.7	250%	300%	15.55547 sq.ft.lb	15 s	643 lb	68 dB(A)	1.15	1780 rpm	94.5	94.5	95	0.74	0.83	0.85	155/140/69.9 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	60	364TS	Standard Frame	6.7	250%	300%	15.55547 sq.ft.lb	15 s	825 lb	68 dB(A)	1.15	1780 rpm	94.5	94.5	95	0.74	0.83	0.85	155/140/69.9 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	60	364/ST	Standard Frame	6.7	250%	300%	15.55547 sq.ft.lb	15 s	643 lb	68 dB(A)	1.15	1780 rpm	94.5	94.5	95	0.74	0.83	0.85	155/140/69.9 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	75	365T	Standard Frame	6.7	210%	260%	19.51434 sq.ft.lb	14 s	648 lb	68 dB(A)	1.15	1780 rpm	94.5	95	95	0.76	0.84	0.87	189/167/83.5 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	4	75	365TS	Standard Frame	6.7	210%	260%	19.51434 sq.ft.lb	14 s	825 lb	68 dB(A)	1.15	1780 rpm	94.5	95	95	0.76	0.84	0.87	189/167/83.5 A	1000 m	S1	-20°C +40°C	IP23
NEMA	TEFC	60 Hz	208-230/460V	4	3	182T	Reduced Frame	8.1	230%	340%	0.34005 sq.ft.lb	23 s	90.4 lb	56 dB(A)	1.25	1760 rpm	87.5	88.5	89.5	0.61	0.73	0.79	8.65/7.82/3.91 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	3	182/4T	Standard Frame	8.1	230%	340%	0.34005 sq.ft.lb	23 s	90.4 lb	56 dB(A)	1.25	1760 rpm	87.5	88.5	89.5	0.61	0.73	0.79	8.65/7.82/3.91 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	3	184T	Standard Frame	8.1	230%	340%	0.34005 sq.ft.lb	23 s	90.4 lb	56 dB(A)	1.25	1760 rpm	87.5	88.5	89.5	0.61	0.73	0.79	8.65/7.82/3.91 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	5	182/4T	Standard Frame	7.2	230%	320%	0.40032 sq.ft.lb	15 s	94.8 lb	56 dB(A)	1.25	1755 rpm	88.5	89.5	89.5	0.62	0.74	0.8	14.3/12.9/6.45 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	5	184T	Standard Frame	7.2	230%	320%	0.40032 sq.ft.lb	15 s	94.8 lb	56 dB(A)	1.25	1755 rpm	88.5	89.5	89.5	0.62	0.74	0.8	14.3/12.9/6.45 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	5	213T	Superior Frame	7.1	230%	320%	1.07473 sq.ft.lb	20 s	132 lb	58 dB(A)	1.25	1765 rpm	88.5	89.5	89.5	0.64	0.75	0.81	14.2/12.8/6.41 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	7.5	213T	Reduced Frame	7.1	220%	310%	1.34359 sq.ft.lb	20 s	154 lb	58 dB(A)	1.25	1765 rpm	89.5	91	91.7	0.66	0.76	0.82	19.9/18.4/9.18 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	7.5	213/ST	Standard Frame	7.1	220%	310%	1.34359 sq.ft.lb	20 s	154 lb	58 dB(A)	1.25	1765 rpm	89.5	91	91.7	0.66	0.76	0.82	19.9/18.4/9.18 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	7.5	215T	Standard Frame	7.1	220%	310%	1.34359 sq.ft.lb	20 s	154 lb	58 dB(A)	1.25	1765 rpm	89.5	91	91.7	0.66	0.76	0.82	19.9/18.4/9.18 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	10	213/ST	Standard Frame	6.4	200%	300%	1.51041 sq.ft.lb	17 s	172 lb	58 dB(A)	1.25	1765 rpm	91	91.7	91.7	0.66	0.77	0.83	27.4/24.8/12.4 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	10	215T	Standard Frame	6.4	200%	300%	1.51041 sq.ft.lb	17 s	172 lb	58 dB(A)	1.25	1765 rpm	91	91.7	91.7	0.66	0.77	0.83	27.4/24.8/12.4 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	15	254T	Reduced Frame	6.4	230%	270%	2.61979 sq.ft.lb	17 s	251 lb	64 dB(A)	1.25	1765 rpm	91	91.7	92.4	0.68	0.78	0.83	39.8/36.0/18.0 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	15	254/ST	Standard Frame	6.4	230%	270%	2.61979 sq.ft.lb	17 s	251 lb	64 dB(A)	1.25	1765 rpm	91	91.7	92.4	0.68	0.78	0.83	39.8/36.0/18.0 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	15	256T	Standard Frame	6.4	230%	270%	2.61979 sq.ft.lb	17 s	251 lb	64 dB(A)	1.25	1765 rpm	91	91.7	92.4	0.68	0.78	0.83	39.8/36.0/18.0 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	20	254/ST	Standard Frame	6.5	230%	270%	3.09629 sq.ft.lb	15 s	291 lb	64 dB(A)	1.25	1765 rpm	91.7	92.4	93	0.68	0.79	0.84	53.3/48.2/24.1 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	20	256T	Standard Frame	6.5	230%	270%	3.09629 sq.ft.lb	15 s	291 lb	64 dB(A)	1.25	1765 rpm	91.7	92.4	93	0.68	0.79	0.84	53.3/48.2/24.1 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	20	284T	Superior Frame	6	230%	260%	5.10835 sq.ft.lb	27 s	370 lb	64 dB(A)	1.25	1765 rpm	92.4	93	93	0.7	0.8	0.84	53.3/48.2/24.1 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	20	284TS	Superior Frame	6	230%	260%	5.10835 sq.ft.lb	27 s	370 lb	64 dB(A)	1.25	1765 rpm	92.4	93	93	0.7	0.8	0.84	53.3/48.2/24.1 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	20	284/ST	Standard Frame	6	230%	260%	5.10835 sq.ft.lb	27 s	370 lb	64 dB(A)	1.25	1765 rpm	92.4	93	93	0.7	0.8	0.84	53.3/48.2/24.1 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	25	284T	Reduced Frame	6.2	240%	270%	5.10835 sq.ft.lb	24 s	388 lb	64 dB(A)	1.25	1765 rpm	92.4	93	93.6	0.7	0.8	0.84	65.2/59.0/29.5 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	25	284TS	Reduced Frame	6.2	240%	270%	5.10835 sq.ft.lb	24 s	388 lb	64 dB(A)	1.25	1765 rpm	92.4	93	93.6	0.7	0.8	0.84	65.2/59.0/29.5 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	25	284/ST	Standard Frame	6.2	240%	270%	5.10835 sq.ft.lb	24 s	388 lb	64 dB(A)	1.25	1765 rpm	92.4	93	93.6	0.7	0.8	0.84	65.2/59.0/29.5 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	25	284/6TS	Standard Frame	6.2	240%	270%	5.10835 sq.ft.lb	24 s	388 lb	64 dB(A)	1.25	1765 rpm	92.4	93	93.6	0.7	0.8	0.84	65.2/59.0/29.5 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	25	286T	Standard Frame	6.2	240%	270%	5.10835 sq.ft.lb	24 s	388 lb	64 dB(A)	1.25	1765 rpm	92.4	93	93.6	0.7	0.8	0.84	65.2/59.0/29.5 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	30	284/ST	Standard Frame	6.1	240%	240%	5.85323 sq.ft.lb	20 s	437 lb	64 dB(A)	1.25	1765 rpm	93	93	93.6	0.7	0.8	0.84	77.6/70.2/35.1 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V	4	30	284/6TS	Standard Frame	6.1	240%	240%	5.85323 sq.ft.lb	20 s	437 lb	64 dB(A)	1.25	1765 rpm	93	93	93.6	0.7	0.8	0.84	77.6/70.2/35.1 A	1000 m	S1	-20°C +40°C	IP55
NEMA	TEFC	60 Hz	208-230/460V																								



Standard	Type	Frequency	Voltage	Poles	Output HP	Frame	Locked rotor current (l/l/m)	Locked rotor torque	Breakdown torque	Moment of inertia	Locked rotor time	Weight	Noise level	Service Factor	Full load speed	Efficiency (%)			Power factor			Rated current	Altitude	Duty	Ambient temperature	Degree of Protection	
																50%	75%	100%	50%	75%	100%						
NEMA	ODP	60 Hz	208-230/460V	2	20	254T	Standard Frame	6	190%	250%	0.73278 sq.ft.lb	12 s	203 lb	66 dB(A)	1.15	3520 rpm	89.5	90.2	91	0.71	0.8	0.84	54.4/49.2/24.6 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	25	256T	Standard Frame	6.5	200%	260%	1.08185 sq.ft.lb	9 s	242 lb	67 dB(A)	1.15	3530 rpm	91	91.7	91.7	0.73	0.82	0.85	65.9/59.6/29.8 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	30	284TS	Standard Frame	6.4	220%	280%	1.88558 sq.ft.lb	10 s	299 lb	72 dB(A)	1.15	3540 rpm	92.4	93	92.4	0.77	0.84	0.86	76.7/69.4/34.7 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	40	286TS	Standard Frame	6.4	200%	260%	2.35686 sq.ft.lb	10 s	357 lb	73 dB(A)	1.15	3535 rpm	91.7	93	93	0.74	0.83	0.86	104/94.2/47.1 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	50	324TS	Standard Frame	6.4	220%	260%	3.83120 sq.ft.lb	28 s	532 lb	74 dB(A)	1.15	3555 rpm	92.4	93.6	93.6	0.74	0.82	0.84	131/118/59.1 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	60	326TS	Standard Frame	6.2	200%	260%	4.36347 sq.ft.lb	24 s	526 lb	75 dB(A)	1.15	3555 rpm	93	93.6	93.6	0.77	0.84	0.85	157/142/71.0 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	75	364TS	Standard Frame	6.5	180%	280%	6.81074 sq.ft.lb	14 s	526 lb	80 dB(A)	1.15	3550 rpm	93.6	94.1	94.1	0.83	0.88	0.9	180/163/81.5 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	100	365TS	Standard Frame	6.7	190%	280%	8.30074 sq.ft.lb	12 s	587 lb	83 dB(A)	1.15	3550 rpm	94.1	94.5	94.5	0.84	0.89	0.9	245/222/111 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	125	404TS	Standard Frame	6.5	180%	280%	10.21623 sq.ft.lb	11 s	985 lb	84 dB(A)	1.15	3550 rpm	94.1	94.5	94.5	0.86	0.89	0.9	301/272/136 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	150	405TS	Standard Frame	6.6	190%	250%	11.91885 sq.ft.lb	10 s	1246 lb	84 dB(A)	1.15	3555 rpm	94.5	94.5	94.5	0.86	0.89	0.9	356/324/162 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	200	444TS	Standard Frame	6.5	190%	250%	25.68912 sq.ft.lb	20 s	1537 lb	88 dB(A)	1.15	3575 rpm	93.6	94.5	95	0.81	0.87	0.89	493/446/223 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	250	445TS	Standard Frame	6	190%	250%	30.15676 sq.ft.lb	18 s	1806 lb	88 dB(A)	1.15	3564 rpm	94.1	95	95	0.84	0.88	0.9	602/544/272 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	300	445TS	Standard Frame	6.3	200%	260%	33.50767 sq.ft.lb	16 s	2006 lb	89 dB(A)	1.15	3565 rpm	94.5	95.4	95.4	0.84	0.89	0.9	712/644/322 A	1000 m	S1	-20°C +40°C	IP23
NEMA	ODP	60 Hz	208-230/460V	2	350	447/9TS	Standard Frame	6.5	170%	250%	35.74161 sq.ft.lb	14 s	1819 lb	87 dB(A)	1.15	3565 rpm	95	95.4	95.4	0.83	0.88	0.89	849/768/384 A	1000 m	S1	-20°C +40°C	IP23
NEMA	TEFC	60 Hz	208-230/460V	2	25	284TS	Reduced Frame	6.3	200%	250%	2.69359 sq.ft.lb	17 s	362 lb	72 dB(A)	1.25	3535 rpm	91	91.7	91.7	0.82	0.87	0.89	63.0/57.0/28.5 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	25	284/6T	Standard Frame	6.3	200%	250%	2.69359 sq.ft.lb	17 s	362 lb	72 dB(A)	1.25	3535 rpm	91	91.7	91.7	0.82	0.87	0.89	63.0/57.0/28.5 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	25	284/6TS	Standard Frame	6.3	200%	250%	2.69359 sq.ft.lb	17 s	362 lb	72 dB(A)	1.25	3535 rpm	91	91.7	91.7	0.82	0.87	0.89	63.0/57.0/28.5 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	25	286TS	Superior Frame	6.3	200%	250%	2.69359 sq.ft.lb	17 s	362 lb	72 dB(A)	1.25	3535 rpm	91	91.7	91.7	0.82	0.87	0.89	63.0/57.0/28.5 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	30	284/6T	Standard Frame	6.3	200%	250%	3.36705 sq.ft.lb	15 s	392 lb	72 dB(A)	1.25	3535 rpm	91.7	91.7	91.7	0.82	0.87	0.89	74.8/67.6/33.8 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	30	284/6TS	Standard Frame	6.3	200%	250%	3.36705 sq.ft.lb	15 s	392 lb	72 dB(A)	1.25	3535 rpm	91.7	91.7	91.7	0.82	0.87	0.89	74.8/67.6/33.8 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	30	286TS	Standard Frame	6.3	200%	250%	3.36705 sq.ft.lb	15 s	392 lb	72 dB(A)	1.25	3535 rpm	91.7	91.7	91.7	0.82	0.87	0.89	74.8/67.6/33.8 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	40	324TS	Reduced Frame	6.3	230%	240%	4.89549 sq.ft.lb	22 s	547 lb	78 dB(A)	1.25	3555 rpm	91.7	92.4	92.4	0.82	0.87	0.89	101/91.6/45.8 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	40	324/6TS	Standard Frame	6.3	230%	240%	4.89549 sq.ft.lb	22 s	547 lb	78 dB(A)	1.25	3555 rpm	91.7	92.4	92.4	0.82	0.87	0.89	101/91.6/45.8 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	40	326TS	Superior Frame	6.3	230%	240%	4.89549 sq.ft.lb	22 s	547 lb	78 dB(A)	1.25	3555 rpm	91.7	92.4	92.4	0.82	0.87	0.89	101/91.6/45.8 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	50	324/6TS	Standard Frame	6.2	220%	230%	5.74692 sq.ft.lb	23 s	584 lb	78 dB(A)	1.25	3550 rpm	93	93	93	0.83	0.87	0.89	124/112/56.1 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	50	326TS	Standard Frame	6.2	220%	230%	5.74692 sq.ft.lb	23 s	584 lb	78 dB(A)	1.25	3550 rpm	93	93	93	0.83	0.87	0.89	124/112/56.1 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	60	364/5TS	Standard Frame	6.6	200%	260%	10.64194 sq.ft.lb	14 s	825 lb	79 dB(A)	1.25	3560 rpm	91.7	93	93.6	0.81	0.88	0.9	148/134/67.0 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	60	404/5TS	Superior Frame	6.5	200%	250%	10.64194 sq.ft.lb	22 s	910 lb	79 dB(A)	1.25	3555 rpm	91.7	93	93.6	0.82	0.88	0.9	148/134/67.0 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	75	364/5TS	Standard Frame	6.7	200%	260%	11.91885 sq.ft.lb	10 s	847 lb	79 dB(A)	1.25	3555 rpm	92.4	93.6	93.6	0.83	0.88	0.9	181/164/81.9 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	100	404/5TS	Standard Frame	6.5	200%	240%	13.19600 sq.ft.lb	14 s	1045 lb	79 dB(A)	1.25	3545 rpm	93	94.1	94.1	0.85	0.9	0.91	243/220/110 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	125	444/5TS	Standard Frame	6.6	200%	250%	33.50767 sq.ft.lb	29 s	1598 lb	81 dB(A)	1.15	3570 rpm	93.6	94.5	95	0.82	0.87	0.89	296/268/134 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	150	444/5TS	Standard Frame	6.5	180%	240%	39.09228 sq.ft.lb	22 s	1709 lb	81 dB(A)	1.15	3570 rpm	94.1	95	95	0.83	0.88	0.9	356/322/161 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	200	445/7TS	Standard Frame	6.5	210%	230%	44.67689 sq.ft.lb	14 s	1914 lb	81 dB(A)	1.15	3570 rpm	95	95.4	95.4	0.86	0.89	0.9	484/438/219 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	200	447/9TS	Superior Frame	6.5	200%	250%	44.67689 sq.ft.lb	17 s	2167 lb	81 dB(A)	1.15	3575 rpm	94.1	95	95.4	0.81	0.87	0.89	491/444/222 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	200	504/5TS	Superior Frame	6.8	200%	270%	44.67689 sq.ft.lb	17 s	2167 lb	81 dB(A)	1.15	3575 rpm	94.1	95	95.4	0.81	0.87	0.89	491/444/222 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	250	445/7TS	Reduced Frame	6.5	210%	230%	50.26150 sq.ft.lb	18 s	2158 lb	81 dB(A)	1.15	3565 rpm	95.4	95.8	95.8	0.87	0.9	0.91	588/532/266 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	250	447/9TS	Standard Frame	6.5	230%	220%	50.26150 sq.ft.lb	18 s	2158 lb	81 dB(A)	1.15	3570 rpm	95.4	95.8	95.8	0.87	0.9	0.91	588/532/266 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	250	504/5TS	Superior Frame	7	200%	240%	50.26150 sq.ft.lb	23 s	2388 lb	81 dB(A)	1.15	3575 rpm	95	95.8	95.8	0.85	0.89	0.9	595/538/269 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	300	447/9TS	Standard Frame	6.8	210%	240%	58.08006 sq.ft.lb	14 s	2544 lb	81 dB(A)	1.15	3570 rpm	95.4	95.8	95.8	0.86	0.89	0.9	708/640/320 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	300	586/7TS	Superior Frame	6.5	160%	220%	122.70911 sq.ft.lb	35 s	3382 lb	84 dB(A)	1.15	3580 rpm	95	95.8	95.8	0.87	0.9	0.91	701/634/317 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	350	447/9TS	Reduced Frame	7	240%	250%	68.13231 sq.ft.lb	10 s	2701 lb	81 dB(A)	1.15	3570 rpm	95.4	96.2	96.2	0.85	0.89	0.9	834/754/377 A	1000 m	S1	-20°C +40°C	IP55
NEMA	ODP	60 Hz	208-230/460V	2	350	586/7TS	Standard Frame	6.6	160%	230%	136.34340 sq.ft.lb	28 s	3620 lb	84 dB(A)	1.15	3580 rpm	95.4	96.2	96.2	0.86	0.9	0.91	825/746/373 A	1000 m	S1	-20°C +40°C	IP55